

11/2" (40mm)

21/2" (65mm)

UL Listed Fire Hose









SFFECO UL Listed Single and Double Jacket Fire Hoses are lined with a high-tech EPDM tube whose engineering design guarantees minimum weight with maximum durability and flexibility. The polyester construction is mildew & root-proof, tough, dependable, light weight and with outstanding abrasion resistance with our innovative Wisentec coating. The jacket is evenly and firmly woven and free from visible defects, thread knots, lumps and irregularities of twist. The most common use of these fire hoses are for exterior fire protection and are also used by Fire Brigades.

Features:

- Heavy duty construction for optimum abrasion resistance.
- Weather, ozone and ageing resistant with long service life.
- Easy to repair, clean and maintenance.
- The breaking strength of the jacket threads meets the requirements of UL19.
- The tensile strength and ultimate elongation of inner lining meet the requirements of UL19.
- ❖ Hose is designed to withstand 1½ times the service pressure without rupturing or breaking any thread in the jacket as per UL19.
- ❖ Hose comes with attached couplings, Brass or Chrome Finish as per request.
- Couplings are available in NST or instantaneous BS336 as per request.

Single Jacketed Fire Hose:

	Part No.	Hose Size	Working Pressure	Proof Pressure
	SFSJ40R-UL*	1½″	200 psi	600 psi
SF	D-FH-SJ40HR**	1½″	250 psi	500 psi
	SFSJ65R-UL*	2½″	200 psi	600 psi

Double Jacketed Fire Hose:

Part No.	Hose Size	Working Pressure	Proof Pressure
SFDJ40R-UL*	1½″	300 psi	900 psi
SFDJ65R-UL*	2½″	300 psi	900 psi

OF FISHED 1 I/V ADDIOVED	UL	Listed	**FM Approved	d
--------------------------	----	--------	---------------	---

Color :		
Red	Yellow	White
Hose Length:		
15 M	30 M	M

شركة المصنع السعودى لأجهزة الإطفاء SAUDI FACTORY FOR FIRE EQUIPMENT Co. NOTE: In line with our policy of continuous product improvement, SFFECO reserves the right to modify specifications without prior notice.

