

MOBILE Dry Powder Fire Extinguishing Trailer



MODEL NUMBER
SP 250





CAPACITY
250 Kg

WORKING PRESSURE
13 Bar

POWDER DISCHARGE
**Two Units of 20 Meter
Hose with Pistol Nozzle**

Applications:

- ▶ Petrochemical & Chemical Industries
- ▶ Energy Supply Installation
- ▶ Airports
- ▶ Factories
- ▶ Shipping and Warehousing Facilities
- ▶ Fuel Depots
- ▶ Military Bases, etc.

 A	 B	 C	
CLASS A FIRES Fires involving freely burning materials. i.e. Wood, Paper, Textiles and other carbonaceous materials.	CLASS B FIRES Fires involving flammable liquids. i.e. Petrols and Spirits. NOT ALCOHOL OR COOKING OIL.	CLASS C FIRES Fires involving flammable gasses. i.e. Propane and Butane.	ELECTRICAL FIRES Fires caused by electrical equipment where electric current may be present.

Extinguishing Agent Container:

Pressure container made of special oiled steel sheet according to international specification of pressurized vessels, equipped with filling hole, safety valve and pressure gauge to indicate pressure in the cylinder under operation.

Nitrogen Cylinder:

Pressurized by compressed nitrogen; cylinder provided with regulator.

Trailer Chassis and Superstructures:

The traveling mechanism comprise one torsion bar spring axle two wheels. Vertically adjustable tow bar with towing eye. Equipped with tubeless rubber tyres and vertically adjustable traction pole, 2 mudguards, 2 hose boxes each hose length 20 M with special dry powder gun. Lightings on rear available upon special request.



شركة المصنع السعودي لأجهزة الإطفاء
SAUDI FACTORY FOR FIRE EQUIPMENT Co.



WWW.
SFFECO.com