

# VUFZ.EX16300 - NOZZLES, SPRAY HOSE, PORTABLE

## Nozzles, Spray Hose, Portable

See General Information for Nozzles, Spray Hose, Portable

### SAUDI FACTORY FOR FIRE EQUIPMENT FZCO

EX16300

S-10833

JEBEL ALI FREE ZONE

AUTHORITY SOUTH 1

DUBAI, UNITED ARAB EMIRATES

Model No.	Fire Type	Size, in.	Max Inlet Pressure, psig	Rated Operating Pressure, psig	Rated Flow at Rated Operating Pressure, gpm	Flow in Wide Open Position at 100 psig, gpm
<b>Basic spray nozzles</b>						
<i>SFD-NH-83-40</i>	Class A and B	1-1/2	200	100	104	104
<i>SFD-NH-65</i>	Class A and B	2-1/2*	200	100	280	280
<i>SFD-NH-40</i>	Class A and B	1-1/2**	200	100	130	130

\*Includes both NH (NST) and NPSH (IPT) inlet thread configurations. Also includes BS 336 "Morris" instantaneous coupling inlet configuration.

\*\*Includes both NH (NST) and NPSH (IPT) inlet thread configurations.

Trademark and/or Tradename: "SFFECO",



Last Updated on 2018-03-06

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"