



SFFECO Mobile carbon dioxide fire extinguishers are known for its high reliable performance. The cylinders of CO₂ fire extinguishers are seamless and are extruded from high grade Chrome Molybdenum Steel or Manganese or Carbon Steel.

Suitable to use on Class B and Electrical fires.

The CO₂ extinguisher is especially effective on electrical fires because, being a gas; it does not leave any residues which might further harm the damaged equipment.

Class of Fire



Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.



Fires on electrical plants.



Note:

Model TC10, TC25 and TC30 are SASO Approved

Model	TC10	TC25	TC30	TC60	TCB100
Capacity	10 Kg	25 Kg	30 Kg	60 Kg	45.5 Kg
Total Weight	38 Kg	96 Kg	102 Kg	195 Kg	124.6 Kg
Total Height (mm)	1025	1420	1420	1300	1650
Total Width (mm)	440	590	590	800	590
Total Depth (mm)	940	1310	1310	1600	1500
Hose Length (mm)	3500	3500	3500	5500	6000
Maximum Effective Range (m)	4	6	6	6	6
Duration of Discharge (Sec)	40-50	75-80	90-94	100-110	110-120
Extinguishing Agent	CO ₂				
Testing Pressure (Bar)	250				
Coating	Electrostatic Polyester Powder				
Storage Temperature	-20°C to +60°C				