UL Product iQ®



Clean-agent Extinguishing System Units

COMPANY

SAUDI FACTORY FOR FIRE EQUIPMENT CO

2ND INDUSTRIAL AREA AL-KHARJ RD PO BOX 58469 RIYADH, 11515 Saudi Arabia

EX15997

View model for additional information

Engineered, Halocarbon, System Units(s): FK-5-1-12 engineered extinguishing system units, 500 psig

Engineered, Halocarbon, System Units(s): HFC-227ea engineered extinguishing system units, 25 bar

Engineered, Halocarbon, System Units(s): HFC-227ea engineered extinguishing system units, 360 psig

Engineered, Halocarbon, System Units(s): HFC-227ea engineered extinguishing system units, 360 psig

Engineered, Halocarbon, System Units(s): <u>HFC-227ea engineered extinguishing system units</u>, 42 bar

Engineered, Halocarbon, System Units(s): SFFECO Prime 227, HFC-227ea engineered extinguishing system units incorporating Chinese GB5100/2011 CCCF storage containers, 610 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime 227, HFC-227ea engineered extinguishing system units incorporating DOT/TC storage containers, 360 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime 227, HFC-227ea engineered extinguishing system units incorporating DOT/TC/TPED/TR CU/ISO storage containers, 360, 610, or 725 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime 227, HFC-227ea engineered extinguishing system units incorporating INDIA PESO/IS storage containers, 360, 610, or 725 psig.

Engineered, Halocarbon, System Units(s): <u>SFFECO Prime 227, HFC-227ea engineered extinguishing system units incorporating UN/TC/TPED/TR CU/ISO storage containers, 360, 610, or 725 psig</u>

Engineered, Halocarbon, System Units(s): SFFECO Prime 227, HFC-227ea engineered extinguishing system units incorporating UN/TPED/ISO storage containers, 360, 610, or 725 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime 227, HFC-227ea engineered extinguishing system units incorporating UN/TPED/TR CU/ISO storage containers, 360, 610, or 725 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime 227, HFC-227ea engineered extinguishing system units incorporating UN/TPED/TR CU/ISO/DOT/TC storage containers, 360, 610, or 725 psig.

Engineered, Halocarbon, System Units(s): SFFECO Prime FK, FK-5-1-12 engineered extinguishing system units incorporating DOT/TC storage containers, 360 psig

Engineered, Halocarbon, System Units(s): <u>SFFECO Prime FK, FK-5-1-12 engineered extinguishing system units incorporating DOT/TC/TPED/TR CU/ISO storage containers, 360, 610, or 725 psig</u>

Engineered, Halocarbon, System Units(s): SFFECO Prime FK, FK-5-1-12 engineered extinguishing system units incorporating INDIA PESO/IS storage containers, 360, 610, or 725 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime FK, FK-5-1-12 engineered extinguishing system units incorporating UN/TC/TPED/TR CU/ISO storage containers, 360, 610, or 725 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime FK, FK-5-1-12 engineered extinguishing system units incorporating UN/TPED/ISO storage containers, 360, 610, or 725 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime FK, FK-5-1-12 engineered extinguishing system units incorporating UN/TPED/TR CU/ISO storage containers, 360, 610, or 725 psig

Engineered, Halocarbon, System Units(s): SFFECO Prime FK, FK-5-1-12 engineered extinguishing system units incorporating UN/TPED/TR CU/ISO/DOT/TC storage containers, 360, 610, or 725 psig

Pre-Engineered, Halocarbon, System Units(s): <u>HFC-227ea pre-engineered extinguishing system units, 240/360 psig</u>

Pre-Engineered, Halocarbon, System Units(s): HFC-227ea pre-engineered extinguishing system units, 240/360 psig.

Last Updated on 2023-10-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."